

## 50-HTAS Low Static Solder Wave Masking Tape

This premium paper masking tape is intended for solder wave masking and high temperature paint masking applications. It removes cleanly leaving no residue. It withstands molten solder for 5-8 seconds at 510° F.

### Physical Properties

Backing Material	Crepe kraft paper
Adhesive	Rubber/resin
Color	Tan
Total tape thickness	6.5 mils/0.165mm
Tensile strength	22 lbs./in.
Elongation	7.5%
Adhesion to steel	41oz./in.
Temperature	1.5 hours @ 300° F 2 hours @ 275° F 3 hours @ 250° F

### Specification



### **Part No.**

50-HTAS1-2  
50-HTAS3-4  
50-HTAS1  
50-HTAS15  
50-HTAS2

### **Description**

½" x 60 yds  
¾" x 60 yds  
1" x 60 yds  
1-½" x 60 yds  
2" x 60 yds

### **Related Products:**

ESD Polyimide Tape, ESD Printed Cello Tape, ESD Polyimide Discs, Conductive Shielding Grid Tape



This document is prepared for our customers as a service and is to the best of our knowledge true & accurate. However, it is understood & agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.