

ESD Safe Clipboard

Construction

An ultra-thin 16 mil static dissipative blue solid compostat vinyl.

Chemical Resistance

Resistant to degradation by inorganic acids, organic acids, reducing agents, detergent solutions, alcohols, aliphatic hydrocarbons, mineral oil, amines and aldehydes.

Physical Properties

Color: Blue Emboss Pattern
Size: 9" x 12"
Gauge: 0.016" \pm 0.003"

Tensile: 1000 lb/m-minimum ASTM D412 Die C
Elongation: 150% minimum ASTM D412 Die C

Tear: 125 lb/m-minimum ASTM D624 Die C

Electro-Static Dissipative Properties

Range 1.0 x 10⁹ – 9.9 x 10¹² Ω sq FSD S4.1-1997
Static Decay <0.25 seconds FTS 101C Method 40461 and EIA 541

Suggested Service Temperature

-20°F to +160°F



Part No.	Description
CB0912	9" x 12"

Related Products:

ESD Safe Binders
ESD Sheet Protectors
ESD Shop Travelers



This document is prepared for our customers as a service and is to the best of our knowledge true & accurate. However, it is understood & agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.