KYORENE

SPECIFICATION SHEET 00-001

FEATURES

LINER

Gray **GRAPHENE** Liner, Fine Gauge

COATING

Black **HCT** MicroFoam Nitrile Palm Coating

BENEFITS:

Excellent Abrasion Resistance Food Compliant Anti-Bacterial High Tensile Strength **UV** Resistance Anti-Static Lightweight

CATEGORY:

Graphene

APPLICATIONS:

Aerospace **Appliance Manufacturing Automotive Manufacturing** Construction Logistics Packaging Metal Fabrication Plastic Injection Molding

Armor Guys reference number: 00-001

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)





 ϵ











Oeko-Tex®

SPECIFICATIONS

LINER MATERIALS	Gray Graphene Liner				
COATING MATERIALS	Black HCT MicroFoam Nitrile				
WRIST DESIGN	Continuous Knit				
SIZES	XS -XXL				

PACKAGING								
CASE SIZE	XS	S	М	L	XL	XXL		
PER CARTON	72	72	72	72	72	72		
CUFF COLOR	■ Purple	■Red	Yellow	Brown	■Black	■Blue		
ORIGIN	PRC							

PERFORMANCE LEVEL

EN388: 4121A						
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	Α	В	С	D	E	F
IMPACT	Х	F	Р			

