

610 Presidential Road, Suite 104 Richardson, Texas 75081

Marvelseal 1312 Roll Stock

Meets all the requirements of MIL-PRF-131K, Class 2. MarvelSeal 1312 is heat sealable and can be used for applications requiring protection from light, air, and moisture vapor. MarvelSeal 1312 conforms to FDA Regulations PART 177-1520. QPL Listed.

| <u>Property</u> | Typical Value | Unit of Measure | Test Method |
|---------------------|---------------|--------------------|--------------|
| WVTR | <0.0005 | g/100sq in /24 hrs | ASTM F-1249 |
| OIL RESISTANCE | PASSED | | MIL-STD 3015 |
| TENSILE (MD) | 27 | lb/in | TAPPI T494 |
| TENSILE (CD) | 26 | lb/in | TAPPI T494 |
| ELMENDORF TEAR (MD) | 130 | grams | TAPPI T414 |
| ELMENDORF TEAR (CD) | 152 | grams | TAPPI T414 |
| CALIPER | 0.0077 | inches | TAPPI T411 |



Related Products:

This document is prepared for our customers as a service and is to the best of our knowledge true & accurate. However, it is understood & agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable