



Band Size	Circumference	
	Min.	Max.
Small	5.5" (140mm)	9" (229mm)
Medium	6" (152mm)	11" (279mm)
Large	7" (178mm)	12" (305mm)

Item	Band Size	Coil Cord
<a href="#">2225</a>	Small	Not Included
<a href="#">2226</a>	Medium	Not Included
<a href="#">2227</a>	Large	Not Included
<a href="#">2228</a>	Small	6' ( <a href="#">2234</a> )
<a href="#">2229</a>	Medium	6' ( <a href="#">2234</a> )
<a href="#">2230</a>	Large	6' ( <a href="#">2234</a> )
<a href="#">2231</a>	Small	12' ( <a href="#">2235</a> )
<a href="#">2232</a>	Medium	12' ( <a href="#">2235</a> )
<a href="#">2233</a>	Large	12' ( <a href="#">2235</a> )

Unless otherwise noted, tolerance  $\pm 10\%$

Specifications and procedures subject to change without notice.

- A. .002" polyphenylsulfone sheet laminated to each link. Provides >5,000 Volt RMS insulation per ASTM D149. Will not flake or peel.
- B. Unique dual contact design is to be paired with a [SCS MagSnap™ 360 Coil Cord](#) (not included) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- C. Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- D. Underwriters Laboratory Listing 90P1C.
- E. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.63".
- F. Black ABS plastic insulator separates band into halves.

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

U.S. Patent Pending

### MAGSNAP 360™ DUAL-WIRE METAL EXPANSION WRISTBAND

Distributed By Correct Products, Inc.  
 WEB SITE: [www.correctproducts.com](http://www.correctproducts.com)  
 PHONE (800) 870-1199

**DRAWING NUMBER**  
2225

**DATE**  
August 2015

