


Side Weld Seals 3/8 in.





Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades **Desco's bags are recyclable**

Statshield[®] bags are packaged 100 per package in an oversized shielding bag. Shelf life of bags is minimum one year in normal indoor storage conditions.



STATFREE[®] ESD ULTRA CLEAR BAG



| Specifications | pecifications: |
|----------------|----------------|
|----------------|----------------|

| Electrical Properties | Typical Value | Test Procedures/Method |
|--|---|--|
| Surface Resisitance: (Interior and Exterior) Charge Generation: | < 1 x 10 ¹¹ ohms | Per ANSI/ESD STM11.11 |
| Teflon Quartz | -0.10 (nC/in ²) +0.10 (nC/in ²) | Modified Incline Plane Modified Incline Plane |
| Physical Properties: | | |
| Thickness Width (Inside Dimensions) | Nominal .0035" (.0889mm) ±10% Nominal -0" / + .125" Nominal ± .125" | MIL-STD-3010, 1003 |
| Length (Inside Dimensions) Light Transmission Heat Seal Tensile Strength Puncture Res. MVTR | >90 (%) >8 (lbs/in) >5,300 (MD/TD, psi) >25 lbs 0.35 | STM D-1003 375°F, .75 sec 60 psi ASTM D-882 MIL-STD-3010, 2065 ASTM F-1249 |

Chemical Properties

Polycarbonate compatible: Contains no Amines, Amides, or N-Octanoic Acid.

Bag is free of amines, N-octanoic acid, silicones and heavy metals.

ANSI/ESD S541 Section 6.1 Inside an EPA

"Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

- Low charge generation
- · Dissipative or conductive materials for intimate contact

RoHS 2 and REACH Statement

None of the RoHS 2 restricted materials or REACH substances of very high concern as of 2012/12/19 are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE.

Meets ANSI/ESD S20.20 and Packaging standard ANSI/ESD S541 tested per ANSI/ESD STM11.11


Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc.



Specifications and procedures subject to change without notice.

STATFREE® ESD ULTRA CLEAR BAG, .0035" (.0889mm)

| DISTRIBUTED BY CORRECT PRODUCTS, INC. | |
|--|--|
| www.correctproducts.com (800) 870-1199 | |



© 2013 DESCO INDUSTRIES INC. Employee Owned